



# GasAlert MicroClip

multi-gas detector

## Multi-gas made simple

The slim and compact GasAlertMicroClip provides affordable protection from atmospheric hazards. With simple one-button operation, this multi-gas detector offers ultimate ease of use and significantly reduces time spent training the user. The GasAlertMicroClip is fully compatible with BW's MicroDock II automatic test and calibration system.



H<sub>2</sub>S

CO

O<sub>2</sub>

LEL




**WATER  
RESISTANT** 

**BW**  
Technologies  
by Honeywell

**Wear yellow. Work safe.**

### Standard features of BW products:

- Continuous LCD shows real-time gas concentrations
- Compact and lightweight design makes it comfortable to wear
- Water-resistant
- Simple automatic calibration procedure; compatible with BW MicroDock II automatic test and calibration station
- Full function self-test of sensor, battery status, circuit integrity and audible/visual alarms on start up
- Bright wide-angled visual alarm bars
- Built-in concussion-proof boot

<b>GasAlertMicroClip Specifications</b>																					
<b>Size</b>	4.2 x 2.4 x 1.1 in. / 10.8 x 6.0 x 2.7 cm																				
<b>Weight</b>	5.7 oz. / 160 g																				
<b>Temperature</b>	-4 to +136°F / -20 to +58°C																				
<b>Humidity</b>	0% - 95% RH (non-condensing)																				
<b>Alarms</b>	- Visual, vibrating, audible (95dB) - Low, High, STEL, TWA, OL (over limit)																				
<b>Tests</b>	Audible/visual alarms on activation, sensors, battery and circuitry (continuous)																				
<b>Pump</b>	Compatible with the Sampler motorized sampling pump																				
<b>Typical battery life</b>	12 hours (typical); recharges in less than 3 hours																				
<b>User options</b>	<table border="0"> <tr> <td>Confidence beep</td> <td>Combustible gas measurement (% LEL or % by volume methane)</td> </tr> <tr> <td>Set STEL interval</td> <td>User-settable calibration gas level</td> </tr> <tr> <td>Sensor on/off</td> <td>Force bump test when overdue</td> </tr> <tr> <td>Latching alarms</td> <td>Force calibration when overdue</td> </tr> <tr> <td>Safe display mode</td> <td>Low alarm acknowledge</td> </tr> <tr> <td>Stealth mode</td> <td>Language choices (5)</td> </tr> <tr> <td>Calibration lock</td> <td>Set custom start up message</td> </tr> <tr> <td>Auto zero on start up</td> <td></td> </tr> <tr> <td>O<sub>2</sub> auto calibration on start up</td> <td></td> </tr> <tr> <td>Set bump test interval</td> <td></td> </tr> </table>	Confidence beep	Combustible gas measurement (% LEL or % by volume methane)	Set STEL interval	User-settable calibration gas level	Sensor on/off	Force bump test when overdue	Latching alarms	Force calibration when overdue	Safe display mode	Low alarm acknowledge	Stealth mode	Language choices (5)	Calibration lock	Set custom start up message	Auto zero on start up		O <sub>2</sub> auto calibration on start up		Set bump test interval	
Confidence beep	Combustible gas measurement (% LEL or % by volume methane)																				
Set STEL interval	User-settable calibration gas level																				
Sensor on/off	Force bump test when overdue																				
Latching alarms	Force calibration when overdue																				
Safe display mode	Low alarm acknowledge																				
Stealth mode	Language choices (5)																				
Calibration lock	Set custom start up message																				
Auto zero on start up																					
O <sub>2</sub> auto calibration on start up																					
Set bump test interval																					
<b>Ratings</b>	EMI/RFI: Complies with EMC Directive 89/336/EEC IP 65/67																				
<b>Certifications and approvals</b>	 Class I, Div. 1, Gr. A, B, C, D  American Bureau of Shipping <b>ATEX:</b> CE  II 1 G T4 Ex ia IIC T4 <b>IECEX:</b> Ex ia IIC T4 <b>CE:</b> European Conformity																				
<b>Warranty</b>	Full 2 year warranty including all sensors																				

### Additional GasAlertMicroClip features:

- Tamper-proof, one button operation
- Compatible with the Sampler motorized remote sampling pump
- Equipped with internal vibrating alarm for high noise areas
- Powered by a lithium polymer battery
- Multi-language support in English, French, German, Spanish and Portuguese
- Conveniently manage your fleet using Soft Tools

### Options and Accessories



MicroDock II compatible



Auxiliary Filter Kit



IR Connectivity Kit



Five unit Cradle Charger

For a complete list of accessories, please contact BW Technologies.

### Sensor Specifications

Gas	Measuring Range	Resolution
<b>H<sub>2</sub>S</b>	0-100 ppm	1 ppm
<b>CO</b>	0-500 ppm	1 ppm
<b>O<sub>2</sub></b>	0-30.0%	0.1%
<b>Combustible gases</b>	0-100% LEL 0-5.0% v/v	1% 0.1%

Alarm set points for all sensors are user adjustable. Set point(s) are automatically displayed during instrument start up.

Locally available from

**Optimum Energy Products Ltd.**  
**Online: [www.CanarySense.com](http://www.CanarySense.com)**  
**Toll Free: 1-877-766-5412**



### Corporate Headquarters

2840 - 2 Avenue S.E.  
 Calgary, AB, Canada T2A 7X9  
 Phone: +1-403-248-9226

USA 1.888.749.8878  
 Canada 1.800.663.4164  
 Australia +61.3.9464.2770

Europe +44 (0)1295 700 300  
 France +33 (0) 442 98 17 70  
 Middle East +971-4-8871766

China +86 10 6786 7305  
 S.E. Asia +65 6580 3468  
 Other Countries +1-403-248-9226

[www.CanarySense.com](http://www.CanarySense.com) [info@canarysense.com](mailto:info@canarysense.com)

DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.